	PARISH OF EAST BATON ROUGE		RECEIVED BY:	
	PURCHASING DIVISION		5/27/2022	
			11:00 AM CST	
TITLE: RQ5099-NEW SET BACK TRI-AXLE DUMP		RETURN BID TO:		
TRUCK WITH DUMP BODY		PURCH	ASING DIVISION	
	0.5000	36.00	D	
FILE NO: 5099-22 REQ NO: I	RQ5099	Mailing Address: PO Box 1471	Physical Address: 222 St. Louis Street	
AD DATES. 5/11 0 5/10				
AD DATES: 5/11 & 5/18		Baton Rouge, LA 70821	Baton Rouge, LA	
		70802	Baion Rouge, LA	
			ar & Expedited Mail do not deliver to our	
		physical address; delays may processing	occur due to City-Parish Mailroom	
SHIP TO ADDRESS: City of I			Regarding Inquiries:	
	ks Central Garage	Purchasing Analyst Ar		
	pewa Street	Telephone Number: 22		
Baton Ro	ouge, LA 70805	Email: af	jones@brla.gov	
VENDOR NAME		MAILING ADDRESS		
REMIT TO ADDRESS		CITY, STATE, ZIP		
TELEPHONE NO.	FAX NO.	E-MAIL		
FEDERAL TAX ID OR SOCIAL	SECURITY NUMBER	TITLE		
AUTHORIZED SIGNATURE (R	<mark>Required</mark>)	PRINTED NAME		
QUESTIONS TO BE COMPLE	ETED BY VENDOR:			
QUESTIONS TO BE COME EN	TED DI VENDOM			
1 STATE DELI	IVERY DAYS MAXIMUM	AFTER RECEIPT OF O	RDER	
2. % discount	2 % discount for payment made within 30 days. Discount for payment made in less than 30 days			
	%, or applicable to an inde		will be accepted but not an award	

CITY OF BATON ROUGE

RESPONSES MUST BE

F.O.B.: DESTINATION - PAYMENT TERMS: NET 30

ALL BLANKS ON THIS PAGE SHOULD BE COMPLETED TO AVOID REJECTION OF BID

STATE ENUMERATED ADDENDA RECEIVED (IF ANY)

The signature on this document certifies that proposer has carefully examined the instructions to bidders, terms and specifications applicable to, and made a part of this solicitation. By submission of this document, proposer further certifies that the prices shown are in full compliance with the conditions, terms and specifications of this solicitation. Bid must be signed in the designated space above and by person authorized to sign for bidder

No alterations, changes or additions are allowed on this solicitation, and no additional information, clarifications or other documents are to be included unless specifically required by the specification. Any errors in extensions of prices will be resolved in favor of unit prices submitted.

If services are to be performed in East Baton Rouge City-Parish, evidence of a current occupational license and/or permit issued by the City-Parish shall be supplied by the successful vendor, if applicable.

3.

INVITATION TO BID

INSTRUCTIONS TO BIDDERS / TERMS & CONDITIONS - SEALED BIDS

Bidders are urged to promptly review the requirements of this specification and submit questions for resolution as early as possible during the bid period. Questions or concerns must be submitted in writing to the purchasing division during the bid period. Otherwise, this will be construed as acceptance by the bidders that the intent of the specifications is clear and that competitive bids may be obtained as specified herein. Protests with regard to the specification documents will not be considered after bids are opened.

- 1. Read the entire bid, including all terms and conditions and specifications.
- 2. Bids are mailed only as a courtesy. The City Parish does not assume responsibility for failure of bidders to receive bids. Bidders should rely only on advertisements in the local newspaper, and should personally pick up bids and specifications. Full information may be obtained, or any questions answered, by contacting the Purchasing Division, 222 Saint Louis Street, 8th Floor, Room 826, Baton Rouge, LA 70802 or by calling (225) 389-3259. The City will not accept fax proposals or proposals sent via e-mail. All faxed or e-mailed proposals shall be rejected and returned.
- 3. The bid number, bidder's name, address and bid opening date should be clearly printed or typed on the outside of the bid envelope. Only one bid will be accepted from each bidder for the same job. Alternates will not be accepted unless specifically requested in the proposal. Submission of more than one bid or alternates not requested may be grounds for rejection of all bids by the bidder.
- 4. The method of delivery of bids is the responsibility of the bidder. All bids must be received by the Purchasing Division on or before the specified bid opening date and time. Late bids will not be considered under any circumstances. The City will not accept fax proposals or proposals sent via e-mail. All faxed or e-mailed proposals shall be rejected and returned
- 5. Failure to deliver within the time specified in the bid will constitute a default and may cause cancellation of the contract. Where the city has determined the contractor to be in default, the city reserves right to purchase any or all products or services covered by the contract on the open market and to charge the contractor with cost in excess of the contract price. Until such assessed charges have been paid, no subsequent bid from the defaulting contractor will be considered.
- 6. The City Parish specifically reserves the right to evaluate bids and award items separately, grouped or on an all or none basis, to accept the bid which is in the best interest of the City parish, and to reject all proposals if that is in the best interest of the City Parish.
- 7. Bids submitted through the www.centralbidding.com on-line bidding site, bids shall be accepted only on proposal forms furnished by the City of Baton Rouge and Parish of East Baton Rouge Purchasing Division. The City Parish will only accept bids from those bidders in whose names the proposal forms and/or specifications were issued. Altered or incomplete proposals, or the use of substitute forms or documents, shall render the bid non-responsive and subject to rejection. The entire proposal package, including the specifications and copies of any addenda issued shall be submitted to the Purchasing Division as the bid.
- 8. All bids must be typed or written in ink. Any erasures, strikeover and/or changes to prices should be initialed by the bidder. Failure to initial may be cause for rejection of the bid as non-responsive.
- 9. All bids must be manually signed by a properly authorized party. Failure to do so shall cause the bid to be rejected as non-responsive.
- 10. Where one or more vendor's exact products or typical workmanship is designated as the level of quality desired or equivalent, the Purchasing Division reserves the right to determine the acceptability of any equivalent offered.
- 11. Detailed factory specifications, illustrative literature and any deviations should be submitted with bid as required by the specifications or on the bid form. Representative samples shall be submitted upon request, if appropriate. Bidders proposing an equivalent brand or model should submit with the bid information (such as illustrations, descriptive literature, and technical data) sufficient for the City to evaluate quality, suitability, and compliance with the specifications in the solicitation.
- 12. Written addenda issued prior to bid opening which modifies the bid shall become a part of the bid, and shall be incorporated within the purchase order and/or contract. Only a written interpretation or correction by Addendum

- shall be binding. Bidders shall not rely upon any interpretation or correction given by any other method. Failure to acknowledge receipt of addenda (if any) shall render the bid non- responsive and subject to rejection.
- 13. For Printing solicitations, artwork, dies and/or molds shall become the property of the City Parish Government and must be returned to the Purchasing Division, 222 Saint Louis Street, 8th Floor, Room 826, Baton Rouge, LA 70802, upon completion of the order.
- All applicable chemicals, herbicides, pesticides and hazardous materials must be registered for sale in Louisiana by the Department of Agriculture, State of Louisiana, registered with the EPA and must meet all requirements of Louisiana State Laws. Bidders must submit product label, material safety data sheet and EPA registry number with bid. This information will be required on any subsequent deliveries if there is a change in chemical content or a different product is being supplied. Failure to submit this data may be cause for the bid to be rejected or the contract canceled.
- 15. Delivery of items must be made on time to City Parish final destinations within East Baton Rouge Parish. All freight charges shall be prepaid by vendor. Late deliveries or unsatisfactory performance may be cause to cancel the Purchase Order or contract.
- 16. The State of Louisiana Code of Governmental Ethics places restrictions on awarding contracts or purchase orders to persons who are employed by any agency of the City Parish Government, or any business of which he or his spouse has more than a twenty-five percent (25%) interest. The Code also prescribes other restrictions against conflict of interest and establishes guidelines to assure that appropriate ethical standards are followed. If any question exists regarding potential violation of the Code of Ethics, bidders should contact the Purchasing Division prior to submission of the bid. Any violation of the Code of Ethics shall be grounds for disqualification of bid or cancellation of contract.
- 17. All Prices bid shall remain in effect for a period of at least sixty (60) days. City Parish purchases are excluded from state and local taxes.
- 18. Acceptance of award by vendor, either in writing or by shipment of any article described herein, shall effectuate a contract between City Parish and vendor for the materials described herein, and no additional conditions or amendments shall have any effect unless approved in writing by City Parish.
- 19. Bidders may attend the bid opening, but no information or opinions concerning the ultimate contract award will be given at the bid opening or during the evaluation process. Information pertaining to completed files may be secured by visiting the EBR City Parish Purchasing office during normal working hours.
- 20. The City Parish is an equal opportunity employer, and does not discriminate against anyone on the basis of race, sex, creed, color, religion, national origin, ancestry, reprisal, disability, sexual orientation, marital status or political affiliation.
- 21. In accordance with Louisiana Revised Statutes, a preference may be allowed for equivalent products produced, manufactured or grown in Louisiana and/or firms doing business in the State of Louisiana. Do you claim this preference if allowed? YES ____ NO____. If this preference is claimed, attach substantiating information to the proposal to show the basis for the claim.
- 22. Right To Audit Clause: The Contractor shall permit the authorized representative of the City-Parish to periodically inspect and audit all data and records of the Contractor relating to his performance under this contract.
- 23. Terms and Conditions: This solicitation contains all terms and conditions with respect to the purchase of the goods and/or services specified herein. Submittal of any contrary terms and conditions may cause your bid to be rejected. By signing and submitting a bid, vendor agrees that contrary terms and conditions which may be included in their bid are nullified; and agrees that this contract shall be construed in accordance with this solicitation and governed by the laws of the State of Louisiana as required by Louisiana Law.
- 24. In accordance with the provisions of LA. R.S. 38:2212.9, in awarding contracts after August 15, 2010, any public entity is authorized to reject the lowest bid from, or not award the contract to, a business in which any individual with an ownership interest of five percent or more has been convicted of, or has entered a plea of guilty or **Nolo Contendere** to any state felony crime or equivalent federal felony crime committed in the solicitation or execution of a contract or bid awarded under the laws governing public contracts under the provisions of Chapter

10 of this Title, professional, personal, consulting, and social services procurement under the provisions of Chapter 16 of Title 39 of the Louisiana Revised Statutes of 1950, or the Louisiana Procurement Code under the provisions of Chapter 17 of Title 39 of the Louisiana Revised Statutes of 1950.

25. Certification of no suspension or debarment. By signing and submitting any bid for \$25,000 or more, the bidder certifies that their company, any subcontractors, or principals are not suspended or debarred by the general services administration (GSA) in "Audit Requirements In subpart F of the Office of Management and Budget's uniform administrative requirements, cost principles, and audit requirements for federal awards" (Formerly OMB circular a-133).

A list of parties who have been suspended or debarred can be viewed via the internet at http://www.sam.gov.

- 26. Bid prices shall include delivery of all items F.O.B. destination or as otherwise provided. Bids containing "Payment in Advance" or "C.O.D. requirements may be rejected. Payment is to be made within 30 days after receipt of properly executed invoice or delivery, whichever is later.
- 27. Bidders may attend the bid opening, but no information or opinions concerning the ultimate contract award will be given at the bid opening or during the evaluation process. Bids may be examined within 72 hours after bid opening. Information pertaining to completed files may be secured by visiting the Purchasing Division during normal working hours. Written bid tabulations may be accessed at: http://city.brla.gov/dept/purchase/bidresults.asp.
- 28. Contractor agrees, upon receipt of written notice of a claim of a claim or action, to defend the claim or action, or take other appropriate measure, to indemnify, and hold harmless, the city, its agents and employees from and against all claims and actions for bodily injury, death or property damages caused by fault of the contractor, its officers, its agents, or its employees. Contractor is obligated to indemnify only to the extent of the fault of the contractor, its officers, its agents, or its employees, however the contractor shall have no obligation as set forth with respect to any claim or action from bodily injury, death or property damages arising out of the fault of the City, its officers, its agents, or its employees.
- 29. In accordance with Louisiana Law (R.S. 12:262.1 and 12:1308.2), all corporations and limited liability companies must be in good standing with the Louisiana Secretary of State at the time of execution of the contract.
- 30. Vendors submitting signed bids agree to EEOC compliance and certify that they agree to adhere to the mandates dictated by Title VI and VII of the Civil Right Act of 1964, as amended by the Equal Opportunity Act of 1972, Federal Executive Order 11246, the Federal Rehabilitation Act of 1973, as amended, the Vietnam Era Veteran's Readjustment Assistance Act of 1974, Title IX of the Education Amendments of 1972, the Age Act of 1975, and agrees to abide by the requirements of the Americans with Disabilities Act of 1990.

Bidders must agree to keep informed of and comply with all federal, state and local laws, ordinances and regulations which affect their employees or prospective employees.

31. The City of Baton Rouge, Parish of East Baton Rouge launched a new Enterprise Resource Planning (ERP) system, Vendor Self Service (VSS) via Munis. VSS replaced the legacy vendor database and will be used by all departments and agencies citywide.

Vendor Self-Service (VSS) enables vendors to register and maintain information about their organization for the purpose of doing business with City-Parish and receive notifications of business opportunities. The City-Parish procurement activities are subject to the State of Louisiana Public Bid Law, local city-parish ordinances as well as applicable federal statutes as directed by grant providers. Vendors must be registered to receive bid notifications.

New vendors or existing vendors who need to create a VSS account can do so clicking the Registration link at https://brla.gov/vss. Vendors are encouraged to review the step by step https://www.brla.gov/DocumentCenter/View/4899/Vendor-Self-Service-Registration-Guide-PDF before beginning the registration process which may be assessed at https://www.brla.gov/DocumentCenter/View/4899/Vendor-Self-Service-Registration-Guide-PDF before beginning the registration-Guide-PDF before beginning the registration-Guide-PDF.

Additional information regarding how to do business with EBR City-Parish is available at: https://www.brla.gov/DocumentCenter/View/678.

We also post our scheduled bid openings, as well as unofficial bid tabulations after the bids have opened at http://city.brla.gov/dept/purchase/bids.asp.

Note: Commodity codes are required for setting up your profile. These numbers tell us what commodities and services that you can provide. When agencies request products or services, our buyers pull directly from these numbers to send out solicitations, bids, and quotes. The first 3 numbers are the class numbers; the subclasses are two digit numbers that better describe the commodity or service. For questions regarding commodity codes, please contact purchasing at (225) 389-3259 Ext 0.

Important! - A W-9 Form is required in order to do business with City-Parish. Part of the online enrollment process requires you to upload a completed W-9 form. Please have the completed form in an electronic format so that you can submit it as part of the registration process. The W-9 form can be downloaded from the IRS website. We have created step by step directions on how to properly complete the W-9 Form.

FEDERAL CLAUSES, IF APPLICABLE.

I. Remedies for Breach

Bidder acknowledges that contracts in excess of the simplified purchase threshold (\$150,000.00) shall contain provisions allowing for administrative, contractual, or legal remedies for contractor breaches of the contract terms, and shall provide for such remedial actions as appropriate.

II. Termination and Settlement

Bidder acknowledges that contracts in excess of \$10,000.00 shall contain termination provisions including the manner in which termination shall be effected and the basis for settlement. In addition, such provisions shall describe conditions for termination due to fault and for termination due to circumstances outside of the contractors' control.

III. Access to Records

Bidder acknowledges that all contracts (except those for less than the small purchase threshold) shall include provisions authorizing the recipient, US Funding Agency, the Comptroller General, or any of their duly authorized representatives access to all books, documents, papers, and records of the contractor which are directly pertinent to a specific program for the purpose of making audits, examinations, excerpts, and transcriptions.

IV. Equal Employment Opportunity

Bidder acknowledges that all contracts shall contain provisions requiring compliance with

E.O. 11246, "Equal Employment Opportunity," as amended by E.O. 11375, "Amending Executive Order 11236 Relating to Equal Employment Opportunity," and as supplemented by regulations at 41 CFR part 60, "Office of Federal Contract Compliance Programs, Equal Employment Opportunity, Dept. of Labor.

V. Copeland "Anti-Kickback" Act

Bidder acknowledges that all construction/repair contracts and sub-grants in excess of \$2,000 shall include provisions requiring compliance with the Copeland "Anti-kickback" Act (18 U.S.C. §3141-3148), which provides that each contractor or sub-recipient shall be prohibited from inducing any person employed in the construction, completion, or repair of public work, to give up any part of the entitled.

VI. Davis-Bacon Act

Bidder acknowledges that all construction contracts in excess of \$2,000 shall include a provision for compliance with the Davis-Bacon Act, which requires contractors to pay laborers and mechanics wages at a rate not less than the minimum wages specified in a wage determination made by the Secretary of Labor. Additionally, contractors shall be required to pay wages not less than once a week.

VII. Contract Work Hours and Safety Standards Act

Bidder acknowledges that all construction contracts in excess of \$2,000, and all other contracts involving the employment of mechanics or laborers in excess of \$2,500 shall include provisions for compliance with sections 102 and 107 of the Contract Work Hours and Safety Standards Act, which requires each contractor to compute the wages of every mechanic and laborer on the basis of a standard work week of 40 hours. Work in excess of the standard work week is permissible provided that the worker is compensated at a rate of not less than one and one-half times the basic rate of pay for all hours worked in excess of 40 hours. Section 107 is applicable to construction work and provides that no laborer or mechanic shall be required to work in surroundings or under working conditions that are unsanitary, hazardous, or dangerous.

VIII. Rights to Inventions Made Under a Contract or Agreement

Bidder acknowledges that contracts for the performance of experimental, developmental, or research work shall include provisions providing for the rights of the Federal Government and the recipient in any resulting invention in accordance with 37 CFR part 401, "Rights to Inventions Made by Nonprofit Organizations and the Small Business Firms Under Governments Grants, Contracts, and Cooperative Agreements"

IX. Clean Air Act

Bidder acknowledges that the Clean Air Act (CAA) is the comprehensive federal law regulating air emissions from stationary and mobile sources. Among other things, this law authorizes EPA to establish National Ambient Air Quality Standards (NAAQS) to protect public health and public welfare and to regulate emissions of hazardous air pollutants

X. Clean Water Act.

The contractor hereby agrees to adhere to the provisions which require compliance with all applicable Standards, orders, or requirements issued under section 508 of the clean water act which prohibits the use under non-exempt Federal contracts, grants or loans of facilities included on the EPA list of violating facilities

XI. Energy policy and conservation act

The contractor hereby recognizes the mandatory standards and policies relating to energy Efficiency which is contained in the state energy conservation plan issued in compliance with the energy policy and Conservation act (P.L. 94-163).

Bidders must agree to keep informed of and comply with all federal, state and local laws, ordinances and regulations which affect their employees or prospective employees.

INQUIRY PERIOD

An inquiry period is hereby firmly set for all interested bidders to perform a detailed review of the bid documents and to submit any **written questions** relative thereto. *Without exception*, all questions MUST be in writing.

The City-Parish shall not and cannot permit an open-ended inquiry period, as this creates an unwarranted delay in the procurement cycle and operations of our departments. The City-Parish reasonably expects and requires *responsible and interested* bidders to conduct their in-depth review of the bid document and submit inquiries in a timely manner.

All inquiries shall be received by 5:00p.m. on May 19, 2022. <u>INQUIRIES AND/OR QUESTIONS SHALL</u> NOT BE ENTERTAINED THEREAFTER.

Inquiries are to be directed as follows:

Arvin F. Jones, Senior Purchasing Analyst
City-Parish Purchasing Department
222 St. Louis Street, Room 826 (Hand Delivery)
Baton Rouge, LA 70802
or
P.O.Box 1471
Baton Rouge, LA 70821
or
Emails of innes@byle.gov

Email: afjones@brla.gov or Fax (225) 389-4841

DEALER LICENSE REQUIREMENTS

Any vendor wishing to bid on vehicles for City of Baton Rouge/Parish of East Baton Rouge must be in compliance with Chapter 6, Distribution and Sales of Motor Vehicles, LA State Statute R.S. 32:1251, which stipulates any motor vehicle manufacturer, distributor, dealer and lessor doing business in Louisiana must be licensed in Louisiana.

All bidders shall include a copy of their valid dealer's license, issued under the provisions of R.S. 32:1254, with any bid submitted. Per R.S. 38:2218.8, public entities are prohibited from accepting bids from or entering into any contract or cooperative endeavor agreement or any other transaction for the procurement of vehicles with a dealer who does not possess a valid dealer's license issued pursuant to R.S. 32:1254. A public entity shall reject any bid submitted by a dealer for the purchase of vehicles which does not include a copy of a valid dealer license.

RS 38:2212.8 Prohibition of bids from or contracts with unlicensed dealers

- A. A public entity shall not accept any bid from or enter into any contract or cooperative endeavor agreement, or any other transaction for the procurement of vehicles, with a dealer who does not possess a valid dealer's license issued under the provisions of R.S. 32:1254.
- B. A public entity shall require that any bid submitted by, or a contract or cooperative endeavor agreement with, a dealer for the purchase of vehicles shall include a copy of a valid dealer's license issued under the provisions of R.S. 32:1254.
- C. A public entity shall reject any bid submitted by a dealer for the purchase of vehicles which does not include
- a copy of a valid dealer license.
- D. A public entity shall not sign a contract or cooperative endeavor agreement with a dealer for the purchase of vehicles which does not include a copy of a valid dealer license.
- E. If in the course of an audit or review by the legislative auditor, pursuant to the powers and duties in R.S.
- 24:513, a violation of this Section is found, the legislative auditor shall report such findings to the E. If in the course of an audit or review by the legislative auditor, pursuant to the powers and duties in R.S. 24:513, a violation of this Section is found, the legislative auditor shall report such findings to the Louisiana Motor Vehicle Commission. Acts 2010, No. 376, §1.

CITY OF BATON ROUGE PARISH OF EAST BATON ROUGE PURCHASING DIVISION

Pricing Sheet

The brand and model used in this specification is used only to denote the general style, type, character and quality standard of the supplies requested. Please note the brand and model that you are bidding in the designated spaces provided. If bidding other than specified, sufficient information should be enclosed with the bid to in order to determine quality,

suitability, compatibility and compliance with the specifications.

ITEM	DESCRIPTION	QTY	UNIT	UNIT PRICE	TOTAL
0001	2023 OR NEWER 4700SB TRI-AXLE DUMP HAULING TRUCK WITH DUMP BODY. 2023 OR NEWER WESTERN STAR 47X/49X PRL-26X SB TRI-AXLE DUMP HAULING TRUCK WITH WARREN DUMP BODY OR EQUAL IN ACCORDANCE WITH THE ATTACHED SPECIFICATIONS. State Brand and Model # Bidding:	1 1	EA	\$	\$

Picture only denotes the general style, type, character and quality standard approved

CITY OF BATON ROUGE PARISH OF EAST BATON ROUGE PURCHASING DIVISION

Specifications:

GENRAL: The intent of this proposal is to establish a price for 2023 OR NEWER WESTERN STAR 47X/49X PRL-26X SB TRI-AXLE DUMP HAULING TRUCK OR APPROVED EQUAL. These specifications represent standard requirements for City Parish Public Work Department. Bids are evaluated based on the totality of "Yes" responses. "Yes" response(s) provided by bidders that are found to be incorrect during bid evaluation may result in a determination of bid non-responsiveness.

MINIMUM SPECIFICATIONS: 2023 OR NEWER WESTERN STAR 47X/49X PRL-26X SB TRI-AXLE DUMP HAULING TRUCK WITH DUMP BODY or APPROVED EQUAL. As a minimum (any non-compliance must be marked	M	mply leet ications	Specify any Deviation from listed Specification (size, dimensions, color, brand, etc.)
"NO") each item shall be equipped with, and all components bid must be compatible and upon installation create a fully functional piece of equipment.	YES	NO	
0001 SPECIFICATIONS:			
WESTERN STAR 47X OR APPROVED EQUAL			
2022 OR NEWER			
SET BACK AXLE - TRUCK			
TRAILER TOWING PROVISION AT END OF			
FRAME WITH SAEJ560			
LH PRIMARY STEERING LOCATION			
TRUCK SERVICE:		ı	
End Dump Body			
Ox Bodies (TBEI)			
GOVERNMENT BUSINESS SEGMENT			
EXPECTED FRONT AXLE(S) LOAD: 20000.0 lbs			
EXPECTS) REAR DRIVE AXLE(S) LOAD: 46000.0			
lbs			
ENGINE		ı	
DETROIT DD13 GEN 5 12.8L 410 HP Q 1625			
RPM, 1900 GOV RPM, 1650 LB-FT @ 975 RPM			
ELECTRONIC PARAMETERS	<u> </u>	I	T
70 MPH ROAD SPEED LIMIT			
CRUISE CONTROL SPEED LIMIT 3 MPH HIGHER			
THAN ROAD SPEED LIMIT			
PTO MODE ENGINE RPM LIMIT – 1000 RPM			
PTO RPM CONTROL WITH STEERING WHEEL			
SWITCHES PTO MODE DRM INCREMENT 25 DRM			
PTO MODE RPM INCREMENT - 25 RPM PTO GOVERNOR RAMP RATE - 25 RPM PER-			
SECOND			
ONE DASH MOUNTED PTO SPEED WITH PTO			
SWITCH ENGAGEMENT			
PTO SPEED 1 SETTING - 900 RPM			
PTO MINIMUM RPM - 600			
ENABLE AUTO ENGINE RPM ELEVATE FOR			
EXTENDED IDLE			
PTO 1, DASH SWITCH, STATIONARY			
OPERATION			
		1	ı

2010 EPA/CARB EMISSION CERTIFICATION NO 2008 CARB EMISSION CERTIFICATION ALUMINUM OIL PAN ENGINE MOUNTED OIL CHECK AND FILL SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER LN 12V170 AMP AV1160 PAD MOUNT ALTERNATOR (3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUIDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE. AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION NAD VIRTUAL REGENERATION NEQUEST SWITCH IN CLUSTER AND DASH MOUNTED INIBIIT SWITCH IT FOOT 00 INCH (132 INCH-0-5.5 9 INCH) EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK WONTED INIBIT SWITCH IT FOOT 00 INCH (132 INCH-0-5.5 9 INCH) EXHAUST FLUID TANK WONTED INIBIT SWITCH IT HEAVY DUTY STANDARD DIESEL EXHAUST HUID TANK LOCATION	ENGINE EQUIPMENT	
ALLIMINUM OIL PAN ENGINE MOUNTED OIL CHECK AND FILL SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER LN 12V170 AMP AVI 160 PAD MOUNT ALTERNATOR (3) DINA GENUINE, FLOODED STARTING, MIN 3000CCA, SSSEC, THREADED STUD BATTERIES BATTERY BOX WITH ALLUMINUM COVER MOUNTED SHORT SIDE TO RAIL SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALLUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL, FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGEDERATION AND VIRTUAL REGERERATION AND V	2010 EPA/CARB/GHG21 CONFIGURATION	
INGINE MOUNTED OIL CHECK AND FILL SIDE OF HOOD AR INTAKE WITH ENGINE MOUNTED AIR CLEANER LN 12V170 AMP AV1160 PAD MOUNT ALTERNATOR (3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL. SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAPETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TALLPPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION ARD VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INTEINING HORIZONTAL STERREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION ARD VIRTUAL REGENERATION ARD VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH II FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP II GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	NO 2008 CARB EMISSION CERTIFICATION	
SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER MOUNTED AIR CLEANER LN 12V170 AMP AV1160 PAD MOUNT ALTERNATOR (3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL. SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH II FOOT 00 INCH (132 INCH-0/-5.9 INCH) EXHAUST SYSTEM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER	ALUMINUM OIL PAN	
MOUNTED AIR CLEANER IN 12V170 AMP AV1160 PAD MOUNT ALTERNATOR (3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH-0/-5.9 INCH) EXHAUST SYSTEM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	ENGINE MOUNTED OIL CHECK AND FILL	
IN 12V170 AMP AV1160 PAD MOUNT ALTERNATOR (3) DINA GENUINE, FLOODED STARTING, MIN 3000CCA, 558C, THREADED STUD BATTERIES BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL. SINGLE BATTERY BOX FRAME MOUNTED LH SINGLE BATTERY BOX FRAME MOUNTED LH SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU, RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER	SIDE OF HOOD AIR INTAKE WITH ENGINE	
ALTERNATOR (3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, S5SRC, THREADED STUD BATTERIES BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTRATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHBIT SWITCH II FOOT 00 INCH (132 INCH-0/-5.9 INCH) EXHAUST SYSTEM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROWNED HANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	MOUNTED AIR CLEANER	
(3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTEATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION NAD VIRTUAL REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION COUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH II FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	LN 12V170 AMP AV1160 PAD MOUNT	
3000CCA, 555RC, THREADED STUD BATTERIES BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTRATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTRATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION ON AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION ON AND VIRTUAL REGENERATION ON AND VIRTUAL REGENERATION NO HIBBIT SWITCH II FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROW STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	ALTERNATOR	
3000CCA, 555RC, THREADED STUD BATTERIES BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTRATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTRATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION ON AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION AND VIRTUAL REGENERATION ON AND VIRTUAL REGENERATION ON AND VIRTUAL REGENERATION NO HIBBIT SWITCH II FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROW STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	(3) DTNA GENUINE, FLOODED STARTING, MIN	
MOUNTED SHORT SIDE TO RAIL SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAIL,PIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH II FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST		
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	BATTERY BOX WITH ALUMINUM COVER	
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	MOUNTED SHORT SIDE TO RAIL	
SIDE BACK OF CAB WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST		
CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH-0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	SIDE BACK OF CAB	
CABLES WITH ADDITIONAL FRAME GROUND RETURN UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH-0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	WIRE GROUND RETURN FOR BATTERY	
UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST		
UNPOLISHED ALUMINUM WST BATTERY BOX COVER POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST		
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH II FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	UNPOLISHED ALUMINUM WST BATTERY BOX	
MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTEATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	COVER	
MOUNTED CONTROL SWITCH MOUNTS) OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTEATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	POSITIVE LOAD DISCONNECT WITH CAB	
OUTBOARD DRIVER SEAT POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST		
JUMPSTART LOCATED ON FRAME NEXT TO STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	,	
STARTER BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	POSITIVE AND NEGATIVE POSTS FOR	
BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	JUMPSTART LOCATED ON FRAME NEXT TO	
AIR COMPRESSOR WITH SAFETY VALVE ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	STARTER	
ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	BW MODEL FE-921 19.0 CFM SINGLE CYLINDER	
PROTECTION SYSTEM JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	AIR COMPRESSOR WITH SAFETY VALVE	
JACOBS COMPRESSION BRAKE RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	ELECTRONIC ENGINE INTEGRAL SHUTDOWN	
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	PROTECTION SYSTEM	
HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	JACOBS COMPRESSION BRAKE	
ASSEMBLY WITH RH B-PILLAR MOUNTED VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	RH OUTBOARD UNDER STEP MOUNTED	
VERTICAL TAILPIPE ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	HORIZONTAL AFTERTREATMENT SYSTEM	
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	ASSEMBLY WITH RH B-PILLAR MOUNTED	
AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	VERTICAL TAILPIPE	
REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	ENGINE AFTERTREATMENT DEVICE,	
REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	AUTOMATIC OVER THE ROAD ACTIVE	
CLUSTER AND DASH MOUNTED INHIBIT SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	REGENERATION AND VIRTUAL	
SWTTCH 11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	•	
11 FOOT 00 INCH (132 INCH+0/-5.9 INCH) EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST		
EXHAUST SYSTBM HEIGHT RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST		
RH CURVED VERTICAL TAILPIPE B-PILLAR MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	`	
MOU. RED ROUTED FROM STEP 13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST		
13 GALLON DIESEL EXHAUST FLUID TANK UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST		
UNPOLISHED ALUMINUM WST DIESEL EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST		
EXHAUST FLUID TANK COVER LH HEAVY DUTY STANDARD DIESEL EXHAUST	13 GALLON DIESEL EXHAUST FLUID TANK	
LH HEAVY DUTY STANDARD DIESEL EXHAUST	UNPOLISHED ALUMINUM WST DIESEL	
	EXHAUST FLUID TANK COVER	
FLUID TANK LOCATION		
	FLUID TANK LOCATION	

STANDARD DIESEL EXHAUST FLUID TANK	
CAP	
STAINLESS STEEL AFTERTREATMENT	
DEVICE/MUFFLER/TAILP1PE SHIELD	
ELECTRONICALLY CONTROLLH3 VARIABLE	
SPEED VISCOUS FAN DRIVE	
AUTOMATIC FAN CONTROL WTTHOUT DASH	
SWITCH. NON S4G1NE MOUNTS)	
DETROIT FUEL/WATER SEPARATOR WITH	
BYPASS	
DDC SUPPLIED ENGINE MOUNTED FUEL	
RLTER/FUEL WATER SEPARATOR WITH	
WATER-IN-FUEL INDICATOR	
FULL FLOW OIL FILTER	
1400 SQUARE INCH VOCATIONAL RADIATOR	
ANTIFREEZE TO -34F, OAT (NITRITE AND	
SILICATE FREE) EXTENDED LIFE COOLANT	
GATES BLUE STRIPE COOLANT HOSES OR	
EQUIVALENT	
HDEP FIXED RATIO COOLANT PUMP AND	
RADIATOR DRAIN VALVE	
LOWER RADIATOR GUARD	
MITSUBISHI 12V MOD 3.175-DP60 STARTER	
WITH INTEGRATED MAGNETIC SWITCH	
TRANSMISSION	
ALLISON 4500 RDS AUTOMATIC	
TRANSMISSION WITH PTO PROVISION	
ALLISON VOCATIONAL PACKAGE 223 -	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1,	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1,	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY PRIMARY SHIFT SCHEDULE RECOMMENDED	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE SECONDARY SHIFT SCHEDULE	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE PRIMARY SHIFT SPED RECOMMENDE BY DTNA	
ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS. HS. MH AND TRV ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY SECONDARY MODE GEARS. LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6. AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE	

SECONDARY SHIFT SPEED RECOMMENDED BY	
DTNA AND ALLISON, THIS DEFINE BY ENGINE	
AND VOCATIONAL USAGE	
CUSTOMER INSTALLED CHELSEA 280 SEIES	
PTO	
PTO MOUNTING, LH SIDE OF MAIN	
TRANSMISSION ALLISON	
MAGNETIC PLUGS. ENGINE DRAIN.	
TRANSMISSION DRAIN, AXLE(S) FILL AND	
DRAIN THE ANNUAL PROPERTY OF THE ANNUAL PROPE	
HEAVY DUTY ELECTRONIC TRANSMISSION	
SHIFT CONTROL, COLUMN MOUNTED	
WATER TO OIL TRANSMISSION COOLER	
TRANSMISSION OIL CHECK AND FILL WITH	
ELECTRONIC OIL LEVEL CHECK	
SYNTHETIC TRANSMISSION FLUID (TES-295	
COMPLIANT)	
FRONT AXLE AND EQUIPMENT	
MFS-20-133A 20,000# FL1 71.0 INCH KPI/3.74	
INCH DROP SINGLE FRONT AXLE	
CONMET PRESET PLUS PREMIUM ALUMINUM	
FRONT HUBS	
MERITOR 16.5X6 Q+CAST SPIDER CAM FRONT	
BRAKES, DOUBLE ANCHOR, FABRICATED	
SHOES NON-ASBESTOS FRONT BRAKE UNING	
CONMET CAST IRON FRONT BRAKE DRUMS	
FRONT BRAKE DUST SHIELDS	
FRONT OIL SEALS	
VENTED FRONT HUB CAPS WITH WINDOW,	
CENTER AND SIDE PLUGS - OIL	
HALDEX AUTOMATIC FRONT SLACK	
ADJUSTERS	
DUAL POWER STEERING GEARS, BENDIX 16-	
20K	
4 QUART POWER STEERING RESERVOIR-5	
OIL/AIR POWER STEERING COOLER-5	
CURRENT AVAILABLE SYNTHETIC 75W-90	
FRONT AXLE LUBE	
FRONT SUSPENSION	
20,000# TAPERLEAF FRONT SUSPENSION	
MAINTENANCE FREE RUBBER BUSHINGS -	
FRONT SUSPENSION	
FRONT SHOCK ABSORBERS	
REAR AXLE AND EQUIPMENT	
RT-46-164P 46,000# R-SERIES TANDEM REAR	
AXLE CONMET PRESET PLUS PREMIUM ALUMINUM	
CONVIET FRESET PLUS PREMITUM ALUMINUM	

REAR HUBS	
4.66 REAR AXLE RATIO	
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING	
MXL 1ST MERITOR EXTENDED LUBE MAIN	
DRIVEUNE WITH HALF ROUND YOKES	
DRIVER CONTROLLED TRACTION	
DIFFERENTIAL - BOTH TANDEM REAR AXLES	
(1) INTERAXLE LOCK VALVE, (1) DRIVER	
CONTROLLED DIFFERENTIAL LOCK	
FORWARD-REAR AND REAR-REAR AXLE	
VALVE	
INDICATOR LIGHT FOR EACH DIFFERENTIAL	
LOCKOUT SWITCH	
MERITOR 16^X8.62 O+ CAST SPIDER CAM REAR	
BRAKES, DOUBLE ANCHOR, FABRICATED	
SHOES NON-ASBESTOS REAR BRAKE LINING	
BRAKE CAMS AND CHAMBERS ON FORWARD	
SIDE OF DRIVE AXLE(S) CONMET CAST IRON REAR BRAKE DRUMS	
REAR BRAKE DUST SHIELDS	
REAR OIL SEALS	
BENDIX EVERSURE LONGSTROKE 2-DRIVE	
AXLES SPRING PARKING CHAMBERS	
HALDEX AUTOMATIC REAR SUCK ADJUSTERS	
CURRENT AVAILABLE SYNTHETIC 75W-90	
REAR AXLE LUBE	
STANDARD REAR AXLE BREATHER(S)	
REAR SUSPENSION	
TUFTRAC GEN2 4&000* FEAR SPRING	
SUSPENSION	
85 INCH NOMINAL RIDE HBGHT (480MM	
GLOBAL REFERENCE HEIGHT) AXLE CLAMPING GROUP	
55 INCH AXLE SPACING	
INDICATOR LIGHT AND BUZZER FOR EACH	
REAR SUSPENSION CONTROL SWITCH	
FORE/AFT AND TRANSVERSE CONTROL RODS	
REAR SHOCK ABSORBERS - ONE AXLE	
PUSHER / TAG EQUIPMENT	
HENDRICKSON EX13 COMP13,500# AIR LIFT	
STEERABLE PUSHER SUSPENSION, 15X4	
BRAKES, FF1 AXLE	
HENDRICKSON EX13 COMP 13,500# FF1	
STEERABLE 15X4 BRAKE INTEGRAL PUSHER	
AXLE CONMET PRESET PLUS PREMIUM IRON	
CONMET PRESET PLUS PREMIUM IRON	

PUSHER/TAG HUBS	
(1) DASH VALVE AND (1) GAUGE FOR SINGLE	
LIFT AXLE	
REVERSE LIFT AXLE WIRING WITH LAST	
STATE RETENTION WITH IGNITION OFF	
(1)REGULATOR MOUNTED ON CHASSIS FOR	
SINGLE LIFT AXLE	
HENDRICKSON 15X4 CAM PUSHER/TAG	
BRAKES, DOUBLE ANCHOR, FABRICATED	
SHOES	
NON-ASBESTOS PUSHER/TAG BRAKE LINING	
CONMET CAST IRON PUSHER/TAG BRAKE	
DRUMS	
NO PUSHER/TAG BRAKE DUST SHIELDS	
PUSHER/TAG OIL SEALS	
STEMCO ALUMINUM VENTED PUSHER/TAG	
HUB CAPS WITH WINDOW AND CENTER PLUG.	
OIL	
HALDEX LONGSTROKE PUSHER/TAG AXLE	
SERVICE CHAMBERS	
HALDEX AUTOMATIC PUSHER/TAG SLACK	
ADJUSTERS	
HENDRICKSON EX13 COMP 13.500& AIR LIFT	
STEERABLE PUSHER SUSPENSION	
52 INCH AXLE SPACING PUSHER/TAG	
BRAKE SYSTEM	
BRAKE SYSTEM WARCO 6S/6M ARS WITH TRACTION CONTROL	
WABCO 6S/6M ABS WITH TRACTION CONTROL	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER AIR DRYER MOUNTED UNDER HOOD STEEL AIR BRAKE RESERVOIRS	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER AIR DRYER MOUNTED UNDER HOOD STEEL AIR BRAKE RESERVOIRS PULL CABLES ON ALL AIR RESERVOIR(S)	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER AIR DRYER MOUNTED UNDER HOOD STEEL AIR BRAKE RESERVOIRS PULL CABLES ON ALL AIR RESERVOIR(S) TRALIER CONNECTIONS	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER AIR DRYER MOUNTED UNDER HOOD STEEL AIR BRAKE RESERVOIRS PULL CABLES ON ALL AIR RESERVOIR(S) TRALIER CONNECTIONS AIR CONNECTIONS TO END OF FRAME WITH	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER AIR DRYER MOUNTED UNDER HOOD STEEL AIR BRAKE RESERVOIRS PULL CABLES ON ALL AIR RESERVOIR(S) TRALIER CONNECTIONS AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER AIR DRYER MOUNTED UNDER HOOD STEEL AIR BRAKE RESERVOIRS PULL CABLES ON ALL AIR RESERVOIR(S) TRALIER CONNECTIONS AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER AIR DRYER MOUNTED UNDER HOOD STEEL AIR BRAKE RESERVOIRS PULL CABLES ON ALL AIR RESERVOIR(S) TRALIER CONNECTIONS AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS PRIMARY CONNECTOR/RECEPTACLE WIRED	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER AIR DRYER MOUNTED UNDER HOOD STEEL AIR BRAKE RESERVOIRS PULL CABLES ON ALL AIR RESERVOIR(S) TRALIER CONNECTIONS AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER AIR DRYER MOUNTED UNDER HOOD STEEL AIR BRAKE RESERVOIRS PULL CABLES ON ALL AIR RESERVOIR(S) TRALIER CONNECTIONS AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION	
WABCO 6S/6M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH RHNFORCED NYLON, FABRIC BRAID AND WIRE STD BRAID CHASSIS AIR LINES (2) RELAY VALVES: ONE 5-8 PSI FOR TANDEM AXLE AND ONE 3-4.5 PSI CRACK FOR PUSHER/TAG WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE WABCO OIL COALESCING FILTER FOR AIR DRYER AIR DRYER MOUNTED UNDER HOOD STEEL AIR BRAKE RESERVOIRS PULL CABLES ON ALL AIR RESERVOIR(S) TRALIER CONNECTIONS AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN	

WHEELBASE & FRAME	
5725MM (225 INCH) WHEELBASE	
13.0MM X 87.0MM X 311.0MM STEEL FRAME	
(0.51X3.43X1234 INCH) 120 KSI	
1525MM (60 INCH) REAR FRAME OVERHANG	
FRAME OVERHANG RANGE 51 INCH TO 60	
INCH	
CALCD BACK OF CAB TO REAR SUSP C/L (CA):	
160.24 in	
CALCD FRAME LENGTH - OVERALL: 330.55 in	
FRAME HEIGHT TOP FRONT UNLADEN: 43.88 in	
FRAME HEIGHT TOP FRONT LADEN: 40.7 In	
FRAME HEIGHT TOP REAR UNLADEN: 43.19 in	
FRAME HEIGHT TOP REAR LADEN: 40.78 In	
SQUARE END OF FRAME	
STANDARD WEIGHT ENGINE CROSSMEMBER	
STANDARD CROSSMEMBER BACK OF	
TRANSMISSION	
STANDARD CAST ALUMINUM MIDSHIP	
STANDARD CAST ALUMINUM REARMOST	
CROSSMEMBER	
STANDARD SUSPENSION CROSSMEMBER	
CAST ALUMINUM REAR SUSPENSION	
CROSSMEMBER	
CHASSIS EQUIPMENT	
UNPOLISHED ALUMINUM WST EQUIPMENT	
COVERS	
TEMPORARY STEEL BUMPER	
REMOVABLE FRONT TOW/RECOVERY	
DEVICE.STORED ON CHASSIS FRAME	
HUCK-SPIN ROUND COLLAR CHASSIS	
FASTENERS EXTERIOR HARNESSES WRAPPED IN	
ABRASION TAPE	
FUEL TANKS	
70 GALLON/264 LITER ALUMINUM FUEL TANK	
-LH	
25 INCH DIAMETER FUELTANK(S)	
PLAIN ALUMINUM/PAINTED STEEL	
FUEL/HYDRAUUC TANK(S) WITH PAINTED	
BANDS	
FUELTANK(S) FORWARD	
PLAIN STEP FINISH	
FUEL TANK CAP(S)	
EQUIFLOIN80ARD FUEL SYSTEM	
HIGH TEMPERATURE REINFORCED NYLON	
	I I

FUEL LINE	
TIRES	
MICHELIN XZY-3 385/65R22.5 18 PLY RADIAL	
FRONT TIRES	
MICHELIN XDN2 11R22.5 16 PLY RADIAL REAR	
TIRES	
MICHELIN X MULT1 ENERGY Z2 295/75R22.5 16	
PLY RADIAL PUSHER/TAG TIRES	
WHEELS	
ALCOA LVL ONE 82462X 22.5X12^5 10-HUB	
PILOT 4.68 INSET 10-HAND ALUMINUM DISC	
FRONT WHEELS	
MAXION WHEELS 90541 22.5X8.25 10-HUB PILOT 2-HAND STEEL DISC REAR WHEELS	
MAXION WHEELS 90541 22.5X8.25 10-HUB PILOT	
2-HAND STEEL. DISC PUSHER/TAG WHFRS	
FRONT WHEEL. MOUNTING NUTS	
REAR WHEEL MOUNTING NUTS	
PUSHER/TAG WHEEL MTG NUTS	
CAB EXTERIOR	
111 INCH BBC CONVENTIONALALUMINUM CAB	
STAINLESS STEEL CAB ACCENT MOLDING	
FRONT FENDERS	
BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS	
INTERIOR GRAB HANDLES WITH ADDED	
LOWER LH AND RH A PILLAR GRAB HANDLES	
AND LH AND RH EXTERIOR NON-SUP GRAB	
HANDLES	
BRIGHT HOOD MOUNTED AIR INTAKE GRILLE,	
BLACK SCREEN, WITH LED ACCENT LIGHTS	
X-SERIES STEEL REINFORCED ALUMINUM CAB	
X-SERIES VOCATIONAL HOOD	
HOOD OPENING ASSIST WITH LOCKING STRUT	
WESTERN STAR NAMEPLATES	
DUAL HADLEY SD-978 26 INCH RECTANGULAR	
AIR HORNS	
SINGLE ELECTRIC HORN	
DUAL STAGE INTELLIGENT LED HEADUGHTS	
WITH HEATED LENS SYSTEM	
VISOR MOUNTED LED MARKER LIGHTS	
HEADUGHTS ON WITH WIPERS. WITH	
DAYTIME RUNNING LIGHTS	
INTEGRAL LED STOP/TAIL/BACKUP LIGHTS	
LED SIDE TURN SIGNAL	
C-BAR MIRROR SYSTEM WITH DUAL HEATED	

MIRRORS WITH INTEGRAL HEATED CONVEX,	
DUAL REMOTE, STAINLESS STEEL BACK	
COVER. AND BLACK C-BAR	
102 INCH EQUIPMENT WIDTH	
LH AND RH CONVEX MIRRORS INTEGRAL	
WITH PRIMARY MIRRORS	
RH DOWN VIEW MIRROR	
STANDARD SIDE/REAR REFLECTORS	
UNPOLISHED ALUMINUM WST	
AFTERTREATMENT SYSTEM COVER	
STAINLESS STEEL EXTERIOR SUN VISOR WITH	
INTEGRAL MARKER LIGHTS	
SINGLE SOLAR T1NTED REAR WINDOW, (1) 31	
INCH X 20 INCH	
1-PIECE ROPED4N SOLAR GREEN GLASS	
WINDSHIELD	
8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED. WITH FLUID	
LEVEL INDICATOR	
CAB INTERIOR	
X-SER1ES BASE INTERIOR TRIM LEVEL	
PACKAGE	
CHARCOAL BLACK VINYL BASE LEVEL	
INTERIOR	
CARBON WITH BASE BLACK ACCENT	
BLACK MATS	
(2) DASH MOUNTED POWER OUTLETS AND	
COIN TRAY	
FORWARD ROOF MOUNTED CONSOLE	
LH AND RH DOOR STORAGE POCKETS	
INTEGRATED INTO MOLDED DOOR PANELS	
(2) COAT HOOKS ON BACKWALL OF CAB	
DIGITAL ALARM CLOCK IN DRIVER DISPLAY	
2-1/2 LB. FIRE EXTINGUISHER MOUNTED	
INBOARD OF DRIVER SEAT	
STANDARD HEATER PLUMBING	
RADIATOR MOUNTED AIR CONDITIONER	
CONDENSER	
STANDARD LED CAB LIGHTING	
REMOTE KEYLESS ENTRY AND 2	
TRANSMITTERS	
DOOR LOCKS AND IGNITION SWITCH KEYED	
THE SAME	
KEY QUANTITY OF 3	
LH AND RH ELECTRIC DOOR LOCKS WITH	
AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION	
TROM OF ENTO CLUSED FUSITION	1 1 1
BLACK DOOR HANDLES	

TRIANGULAR REFLECTORS WTTHOUT FLARES	
BASIC 2.0 HIGH BACK AIR SUSPENSION	
DRIVER SEAT WITH 1 CHAMBER AIR LUMBAR,	
INTEGRATED CUSHION EXTENSION AND TILT	
BASIC 2.0 HIGH BACK NON SUSPENSION	
PASSENGER SEAT	
INBOARD DRIVER AND PASSENGER SEAT	
ARMRESTS	
BLACK MORDURA CLOTH DRIVER SEAT	
COVER WITH EMBROIDERED LOGO	
BLACK MORDURA CLOTH PASSENGER SEAT	
COVER WITH EMBROIDERED LOGO	
3 POINT HIGH VISIBILITY ORANGE	
ADJUSTABEL D-RING RETRACTOR DRIVER	
AND FIXED D-RING RETRACTOR PASSENGER	
SEAT BELTS	
ADJUSTABLE TILT AND TELESCOPING	
STEERING COLUMN	
4-SPOKE18 INCH (480MM) BLACK STORING WHEEL WITH SWITCHES	
DRIVER AND PASSENGER INTERIOR SUN	
INTERIOR SUN VISORS	
INSTRUMENTS & CONTROLS	
STANDARD FOOT PEDAL SYSTEM	
ELECTRONIC ACCELERATOR CONTROL	
BLACK GAUGE BEZELS	
STANDARD CENTER INSTRUMENT PANEL	
(1) TRACTOR AND (1) TRAILER BRAKE	
APPLICATION AIR GAUGE	
DUAL NEEDLE PRIMARY AND SECONDARY	
AIR PRESSURE GAUGE	
INTAKE MOUNTS) AIR RESTRICTION	
INDICATOR WITHOUT GRADUATIONS	
97 DB BACKUP ALARM	
ELECTRONIC CRUISE CONTROL WITH STD	
CONTROLS ON STEERING WHEEL SPOKES	
KEY OPERATED IGNITION SWITCH AND	
INTEGRAL START POSITION; 4 POSITION	
OFF/RUN/START/ACCESSORY	
PREMIUM INSTRUMENT CLUSTER WITH 5.0	
INCH TFT COLOR DISPLAY	
DIGITAL PANEL LAMP DIMMER SWITCH IN	
DRIVER DISPLAY HEAVY DUTY ONBOARD DIAGNOSTICS	
INTERFACE CONNECTOR WITH DUST CAP	
LOCATED BELOW LH DASH	
2 INCH ELECTRIC FUEL GAUGE	
FUEL FITER RESTRICTION INDICATOR	
EMISSIONS LIMITED IDLE ADJUST	
10	

ELECTRICAL ENGINE COOLANT	
TEMPERATURE GAUGE	
ENGINE OILTEMPERATURE GAUGE	
ELECTRIC EGINNE OIL PRESSURE GAUGE	
2 INCH TRANSMISSION OILTEMPERATURE	
GAUGE	
ELECTRONIC OUTSIDE TEMPERATURE SENSOR	
DISPLAY IN DRIVER MESSAGE CENTER	
ENGINE TRIP AND PTO HOUR METERS	
INTEGRAL WITHIN DRIVER DISPLAY	
PTO CONTROLS FOR ENHANCED VEHICLE	
ELECTRIC/ELECTRONIC ARCHITECTURE	
NO OBSTACLE DETECTION SYSTEM	
NO VEHICLE STABILITY ADVISOR OR	
CONTROL	
NO LANE DEPARTURE WARNING SYSTEM	
TMC RP1226 ACCESSORY CONNECTOR	
LOCATED BEHIND PASSENGER SIDE	
REMOVEABLE DASH PANEL	
AM/FM/WB WORLD TUNER RADIO WITH	
BLUETOOTH USB AND AUXILIARY INPUTS.	
J1939	
DASH MOUNTED RADIO	
STANDARD SPEAKER SYSTEM	
AM/FM ANTENNA MOUNTED ON RH SIDE	
MIRROR	
POWER AND GROUND WIRING PROVISION	
OVERHEAD	
ROOF/OVERHEAD CONSOLE CB RADIO	
PROVISION	
SINGLE REMOTE SPEAKER WITH LEAD FOR 2-	
WAY RADIO	
SINGLE FIBERGLASS LH MIRROR MOUNTED CB	
ANTENNA WITH BRACKET AND LEAD	
ELECTRONIC MPH SPEEDOMETER WITH	
SECONDARY KPH SCALE, WITHOUT ODOMETER	
ELECTRONIC 2500 RPM TACHOMETER	
DETROIT CONNECT PLATFORM HARDWARE	
5 YEARS DETROIT CONNECT FUEL ANALYTICS	
PACKAGE (INCLUDES BASE PACKAGE	
FEATURES)	
IGNITION SWITCH CONTROLLED ENGINE STOP	
PRE-TRIP INSPECTION FEATURE FOR	
EXTERIOR LAMPS ONLY	
BW TRACTOR PROTECTION VALVE	
TRAILER HAND CONTROL BRAKE VALVE	
2 INCH TURBO AIR PRESSURE GAUGE	

DIGITAL VOLTAGE DISPLAY INTEGRAL WITH	
DRIVER DISPLAY	
ROTARY HEADLAMP SWITCH, MARKER	
LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT	
FOR OPTIONAL FOG/ROAD LAMPS	
TWO VALVE PARKING BRAKE SYSTEM WITH	
DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR	
SELF CANCELING TURN SIGNAL SWITCH WITH	
DIMMER, HEADLAMP FLASH,	
WASH/WIPE/INTERMITTENT	
DUMP BODY	
DUMP BODY - AR ELLIPTICAL - 16' 62" FLUSH	
Yardage: 21/21	
Floor Material: 1/4 AR450	
Front / Material: 62" 1/4 AR450	
Side / Material: 62" 1/4 AR450	
No Vertical Side Brace	
No Horizontal Brace	
Hoist / Cylinder: VTLW-74135	
Hyd Tank: Steel Doghouse Tank (600-80041)	
Hydraulics: 85 CC Gear Pump w DIN Shaft	
Tipping Valve: Chassis Mount	
11 8	
TAIL GATE	
TAIL GATE	
TAIL GATE Yes Air Operated	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame)	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16"	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting:	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting: High Lift Gate: Air Ready (no cylinders)	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting: High Lift Gate: Air Ready (no cylinders) No Side Swing - Ground Operated	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting: High Lift Gate: Air Ready (no cylinders) No Side Swing - Ground Operated No Center Opening	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting: High Lift Gate: Air Ready (no cylinders) No Side Swing - Ground Operated No Center Opening None Material Gate	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting: High Lift Gate: Air Ready (no cylinders) No Side Swing - Ground Operated No Center Opening None Material Gate None Water Tight	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting: High Lift Gate: Air Ready (no cylinders) No Side Swing - Ground Operated No Center Opening None Material Gate None Water Tight DB OPTIONS # 1	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting: High Lift Gate: Air Ready (no cylinders) No Side Swing - Ground Operated No Center Opening None Material Gate None Water Tight DB OPTIONS # 1 Cab-shield: Full Width-1/2 (24")	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting: High Lift Gate: Air Ready (no cylinders) No Side Swing - Ground Operated No Center Opening None Material Gate None Water Tight DB OPTIONS # 1 Cab-shield: Full Width-1/2 (24") Apron: 8" Push Type	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting: High Lift Gate: Air Ready (no cylinders) No Side Swing - Ground Operated No Center Opening None Material Gate None Water Tight DB OPTIONS # 1 Cab-shield: Full Width-1/2 (24") Apron: 8" Push Type No Bolt On	
TAIL GATE Yes Air Operated Panel: 1 (Picture Frame) Material: 1/4 AR450 Height: 62 None Slope Chains: 5/16" Yes Double Acting: High Lift Gate: Air Ready (no cylinders) No Side Swing - Ground Operated No Center Opening None Material Gate None Water Tight DB OPTIONS # 1 Cab-shield: Full Width-1/2 (24") Apron: 8" Push Type No Bolt On	

LIGHTS	
Lights/Harness: LED Lights and Standard Harness	
Oval STT: (1) Grommet Mount STT w/Backup Per	
Posts	
4 comer clear LED flashing light system: (2) in rear	
post & (2) in cab shield DB OPTIONS # 2	
WAR Ladder	
Electric brake controller	
Shovel Rings D/S & P/S	
10" channel bumper w/sight pole BDB1394 pull eye Alum Tread Plate Fenders	
Cap Angles on Sides and Tailgate	
INSTALL	
Yes Hydraulic Hoses/Fittings	
Pump: 22 gal w/air shift CW (400-80263)	
Console: Hyva Deluxe Console	
Yes Conspicuity Tape	
Yes Mudflaps and Brackets	
No Chrome Turnouts	
Yes Splash/Gravel Guards	
No Side Boards	
No Covers	
Yes Wires in Conduit	
No Delivery Fuel/Charges	
Alum Tread Plate Fenders	
Paint	
Warren Black (800-80007) or Equal	
PTO	
POWER TAKE OFF - ALLISON AUTO 4500 or	
Equal	
PTO Muncie MC1 Series (Auto)	
TARP SYSTEM	
TARP system -Installation: Installed	
Brand: Donovan or Equal	
Manual / Electric: Electric	
Type: Arm Aluminum / Steel: Aluminum	
Bent Arm: Yes	
Tarp Size: 90"x18"	
Tarp Type: Mesh	
No Side Flaps	

TOW PACKAGE					
Pintle Plate: 3/4"					
Pintle Hitch: 30 Ton					
Yes Glad Hands					
Yes D Rings					
No Tow Hooks					
Electric Plug: 7 Way					
No Pup Rigging					

DEVIATION NOTES SHOULD BE ATTACHED:

BIDDER'S ORGANIZATION BIDDER IS:

AN INDIVIDUAL

Individual's Name:	
Doing business as:	
Telephone No.:	
A PARTNERSHIP Firm Name:	
Name of person authorized to sign:_	
Title:	
Telephone No.:	Fax No.:
A LIMITED LIABILITY COMPA Company Name:	<u>ANY</u>
Address:	
Telephone No.:	Fax No.:
BID.	A CORPORATION THE CORPORATE RESOLUTION SHOULD BE SUBMITTED WITH
Address:	
State of Incorporation:	
Name of person authorized to sign: _	
Title:	
Telephone No.:	

IF BID IS BY A JOINT VENTURE, ALL PARTIES TO THE BID SHOULD COMPLETE THIS FORM.

CORPORATE RESOLUTION

A meeting of the Board of Directors of		a	corporat	ion
organized under the laws of the State of	and	domici	led	in
was held thisday of, 20 _and was attended				the
Board of Directors.				
The following resolution was offered, duly seconded and after of	liscussion wa	as unanimo	usly adopted	. by
said quorum:				
BE IT RESOLVED, that	is	hereby	authorized	to
submit proposals and execute agreements on behalf of this corp	poration with	the City o	f Baton Rou	ge,
and Parish of East Baton Rouge.				
BE IT FURTHER RESOLVED, that said authorization and ap	pointment sh	all remain	in full force	and
effect, unless revoked by resolution of this Board of Directors	and that sai	d revocation	on will not to	ake
effect until the Purchasing Director of the Parish of East Baton F	Rouge, shall h	nave been f	urnished a co	эру
of said resolution, duly certified.				
I,, hereby certify that I am the Sec	retary of		2	
a corporation created under the laws of the State of	domicile	d in	<u>;</u>	
that the foregoing is a true and exact copy of a resolution adopted	d by a quorur	n of the Bo	ard of Direct	ors
of said corporation at a meeting legally called and held on the	day_of		, 20	, as
said resolution appears of record in the Official Minutes of the B	oard of Direc	etors in my	possession.	
This day of _		20		
SEC	CRETARY		_	